

BORA X Pure Rough PUXU2R

> Web link



Brief description

Surface induction glass ceramic cooktop with extraction

system (matt glass ceramic)

Mode of operation Recirculated air

Article no. 40.002.958.00

VRG 5.56

Price CHF

3985.- O excl. VAT

Product description

BORA surface induction cooktop with integrated cooktop extractor (recirculated air) PUXU2R

Product description

Cooktop

- Matt glass ceramic
- Power level for each cooking zone
- Bridge function
- Timer cooking zones
- Short-term alarm clock
- Residual heat display
- Pot detection
- Pause function
- Warming function
- Parental lock
- Safety shutdown
- Demo mode

Extraction system

- Three-colour sControl+ operation
- Power stage
- Automatic trigger control
- Automatic overrunning
- Cleaning lock
- Filter service indicator
- Front power socket

Scope of delivery

- Surface induction hob with integrated hob extractor recirculated air PUXU2R
- PUXED2 inlet nozzle, black
- Stainless steel grease filter PUEF
- Activated charcoal filter PUAKF
- Operating and intallation instructions
- Drilling template
- Mounting clamps, sealing tape
- Height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

Planning guidelines

- Ensure adequate ventilation under the hob
- Please note that induction-compatible cookware must be used for induction hobs
- Connection cable must be provided by the customer
- Front power socket
- Telescopic pull-out (pull-out up to 80 mm) of the air cleaning box for connection to the rear wall of the carcase.
- For extra-deep cooktop base units, the telescopic pull-out can be extended by 105 mm with the additional PULBTA telescopic pull-out (available as an accessory).

Technical data

Supply voltage

400 V 2N /3N 230 V

Frequency

50 Hz

Maximum power consumption

7,6 kW

Fuse protection / power connection

3 x 16 A



BORA X Pure Rough PUXU2R

> Web link

2 x 16 A

Equipment mass (without duct connections)

830 x 515 x 199 mm

Weight (incl. accessories / packaging)

Material surface

Glass Ceramic

Cooktop

Induction cooking zone front

230 x 230 mm 2100 W

Power level

3000 W

Induction cooking zone rear

230 x 230 mm 2100 W

Power level

3000 W

Power levels

1-9, P

Trigger system

Power levels

1 - 9, P

Connection on exhaust air side

445 × 137 mm

Recirculation filter

Filter medium

Activated carbon with ion exchanger

Filter panel with fine filter

Service life max.

150 h / 1 year

Not compatible with PUED inlet nozzle

Other Articles



40.002.958.00 / CHF 3985.-BORA X Pure Rough PUXU2R



2879.-**BORA Pure PURU**



40.002.955.00 / CHF BORA X Pure PUXA2



40.002.956.00 / CHF BORA X Pure PUXU2



40.002.759.00 / CHF 3068. BORA M Pure PURMA



40.002.760.00 / CHF BORA M Pure PURMU



40.002.065.00 / CHF BORA Pure PURA



40.002.066.00 / CHF



40.002.413.00 / CHF 2124.-BORA S Pure PURSA



40.002.390.00 / CHF 2290.-**BORA S Pure PURSU**