

BORA PKI3 induction glass ceramic hob, Professional 3.0[> Web link](#)

Article no.
40.002.238.00

VRG
2.31
Price CHF
2238.- O excl. VAT

Product description**Product description BORA Professional 3.0 PKI3 induction glass ceramic hob**

Keep warm function
Power level
Bridge function
Residual heat indicator
Pause function
Timer function
Configuration menu
Can be mounted rotated 180°
Cooking zone display on control knob
Demo mode
Pot detection
Automatic cooking system
Digital power level display on the control knob and on the hob
Child safety
Safety switch off

Digital power level display on the hob. Power level display can be installed on the right or left side of the hob (hob can be installed rotated by 180°).

Technical data**Supply voltage**

230 V

Frequency

50 Hz

Maximum power consumption

3,68 kW

Maximum connection value

3,68 kW

Minimum fuse protection

1 x 16 A

Power level

1-9, P

Weight (incl. accessories / packaging)

8,0 kg

Material surface

SCHOTT CERAN

Mains connection

1,5 m

Dimensions (W x D x H)

370 x 540 x 52 mm

Front cooking zone size

230 mm

Front cooking zone performance

2300 W

Front cooking zone power level

3680 W

Rear cooking zone size

165 mm

Rear cooking zone performance

1400 W

Rear cooking zone power level

2200 W

Scope of delivery

Surface induction ceramic glass cooktop PKI3
2 x control knobs
Mounting brackets
Height adjustment plate set
Operating and installation instructions
2 x connection cables Control knob
Connection cable to extractor

BORA PKI3 induction glass ceramic hob, Professional 3.0
[> Web link](#)

Mains connection (L, N, PE) without plug

Planning guidelines

Please note that induction-proof cookware is required for induction cooktops

Please provide sufficient ventilation below the induction cooktop

Planning note for installation in 2 / 1 combinations (2 induction hobs, 1 hob extractor):

Hobs with power level display can be installed either centrally (adjacent to hob extractor on both sides) or facing outwards.

Accessory

Optional accessories



[> Weblink](#)

40.001.767.00 / CHF 97.-
BORA socket USTJ



[> Weblink](#)

40.002.034.00 / CHF 135.-
BORA socket USTJAB
All Black



[> Weblink](#)

40.001.775.00 / CHF 19.-
BORA Glass ceramic
scraper UGS

Compatible Articles






[> Weblink](#)

40.002.244.00 / CHF 111.-
BORA Lock collar
PKR3AB Prof. 3.0



[> Weblink](#)

40.002.243.00 / CHF 74.-
BORA Lock collar PKR3
Prof. 3.0



technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.68 kW
Maximum power rating	3.68 kW
Minimum fuse protection	1 x 16 A
Power supply cable length	1,5 m
Dimensions (width x depth x height)	370 x 540 x 52 mm
Weight (incl. accessories/packaging)	8.0 kg
Surface material	SCHOTT CERAN®
Cooktop power levels	1 - 9, P
Size of front cooking zone	Ø 230 mm
Size of rear cooking zone	Ø 165 mm
Front cooking zone output	2300 W
Rear cooking zone output	1400 W
Front cooking zone power setting output	3680 W
Rear cooking zone power setting output	2200 W

Product description

- Intuitive control knob
- Performance level display on the cooktop
- Variable heat retention function
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- automatic heat up function
- pan size recognition
- Demo mode

Scope of delivery

- Induction cooktop PKI3
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- mounting straps
- height adjustment plate set

product- and planning instructions

- Rotation by 180° possible during installation
- Please note that induction-compatible cookware must be used on induction cooktops
- Ensure sufficient ventilation of the area below the cooktop.