

BORA X Pure PUXU2
[> Web link](#)

Brief description

Surface induction glass ceramic cooktop with extraction system (shiny glass ceramic)

Mode of operation

Recirculated air

Article no.

40.002.956.00

VRG

5.56

Price CHF

3759.- O excl. VAT

Product description
BORA surface induction cooktop with integrated cooktop extractor (recirculated air) PUXU2
Product description
Cooktop

- Shiny glass ceramic
- Power level for each cooking zone
- Bridge function
- Timer cooking zones
- Short-term alarm clock
- Residual heat display
- Pot detection
- Pause function
- Warming function
- Parental lock
- Safety shutdown
- Demo mode

Extraction system

- Three-colour sControl+ operation
- Power stage
- Automatic trigger control
- Automatic overrunning
- Cleaning lock
- Filter service indicator
- Front power socket

Scope of delivery

- Surface induction hob with integrated hob extractor - recirculated air PUXU2
- PUXED2 inlet nozzle, black
- Stainless steel grease filter PUEF
- Activated charcoal filter PUAKF
- Operating and installation instructions
- Drilling template
- Mounting clamps, sealing tape
- Height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

Planning guidelines

- Ensure adequate ventilation under the hob
- Please note that induction-compatible cookware must be used for induction hobs
- Connection cable must be provided by the customer
- Front power socket
- Telescopic pull-out (pull-out up to 80 mm) of the air cleaning box for connection to the rear wall of the carcase.
- For extra-deep cooktop base units, the telescopic pull-out can be extended by 105 mm with the additional PULBTA telescopic pull-out (available as an accessory).

Technical data
Supply voltage

400 V 2N /3N
230 V

Frequency

50 Hz

Maximum power consumption

7,6 kW

Fuse protection / power connection

3 x 16 A

BORA X Pure PUXU2
[> Web link](#)

2 x 16 A

Equipment mass (without duct connections)
830 x 515 x 199 mm

Weight (incl. accessories / packaging)
24,5 kg

Material surface
Glass Ceramic

Cooktop

Induction cooking zone front
230 x 230 mm
2100 W

Power level
3000 W

Induction cooking zone rear
230 x 230 mm
2100 W

Power level
3000 W

Power levels
1-9, P

Trigger system

Power levels
1 - 9, P

Connection on exhaust air side
445 x 137 mm

Recirculation filter

Filter medium
Activated carbon with ion exchanger

Material
Filter panel with fine filter

Service life max.
150 h / 1 year

Not compatible with PUED inlet nozzle

Other Articles

You can find additional articles here [> Weblink](#)



40.002.958.00 / CHF
3985.-
BORA X Pure Rough
PUXU2R



40.002.955.00 / CHF
3593.-
BORA X Pure PUXA2



40.002.956.00 / CHF
3759.-
BORA X Pure PUXU2



40.002.759.00 / CHF
3068.-
BORA M Pure PURMA




40.002.760.00 / CHF
3234.-
BORA M Pure PURMU




40.002.065.00 / CHF
2713.-
BORA Pure PURA



40.002.066.00 / CHF
2879.-
BORA Pure PURU



40.002.413.00 / CHF
2124.-
BORA S Pure PURSA



40.002.390.00 / CHF
2290.-
BORA S Pure PURSU